



Compact design along with flexible AC/DC operation makes the TP series perfect for indoor or outdoor applications.

FEATURES

- ② 1/3,000 external resolution
- ② AC/Battery powered operation
- ② Low battery indication
- ② Clear LCD display
- ② 15 direct PLU memory
- ② Daily total sales report
- ② Change calculating function
- ② Auto power off
- ② Stable, Zero, Net, Low battery designators

OPTIONS

- ② Pole display
- ② Large tray
- ② Rechargeable battery (TP☒)
- ② RS232C (TP☒)
- ② Back light (TP☒)
- ② Dual interval/Triple interval (TP☒)
- ② 200 indirect PLU memory (TP☒)

SPECIFICATIONS

Model	TP Series
Weighing Capacity	6 ; 0.002kg, 15 ; 0.005kg, 30 ; 0.01kg
Display Digits	5/7/8 (Weight/Unit Price/Total Price)
Measurement Type	Load Cell
Power Source	AC 110/120/220/240V, 50/60Hz Battery 1.5V ; 6EA(D Size)
Power Consumption	0.2W
Battery Life	Alkaline Dry Battery : 1000hrs Mn Battery : 500hrs
Operating Temperature	-10 ℃ ; +40 ℃
Platter Size (mm)	332(W) ; 250(D)
Dimensions (mm)	350(W) ; 373(D) ; 122(H)
Product Weight	6.75kg